

# Product datasheet

Specifications



## APC Easy UPS On-Line, 10kVA/10kW, Rackmount 4U, 230V, Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, W/ Rail Kit

SRV10KRIRK

### Overview

<b>Presentation</b>	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	10000 W
<b>Rated power in VA</b>	10000 VA
<b>Output connector type</b>	Hard wire 3-wire (1P + N + E) 1
<b>Number of rack unit</b>	4U
<b>Provided equipment</b>	1 USB cable 1 RS-232 configuration cable 2 rack mounting brackets 2 rack mounting support rails 1 external battery pack 1 battery cable user manual

### General

<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No

### Physical

<b>Colour</b>	Black (RAL 7010)
<b>Height</b>	17.3 cm
<b>Width</b>	43.8 cm
<b>Depth</b>	71.0 cm

<b>Net weight</b>	68 kg
<b>Mounting location</b>	Front
<b>Mounting preference</b>	Lower
<b>Mounting mode</b>	Rack-mounted
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Horizontal

## Input

<b>Input voltage limits</b>	110...300 V 60 % load 176...300 V full load
<b>Number of input connectors</b>	1 hard wire 3-wire (1P + N + E)
<b>Network frequency</b>	40...70 Hz auto sensing

## Output

<b>Maximum configurable power in VA</b>	10000 VA
<b>Maximum configurable power in W</b>	10000 W
<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains
<b>Harmonic distortion</b>	1 %
<b>UPS type</b>	Double conversion online
<b>Wave type</b>	Sine wave
<b>Efficiency</b>	94 % (full load)
<b>Bypass type</b>	Internal bypass (automatic and manual)
<b>Crest factor</b>	3 : 1

## Conformance

<b>Product certifications</b>	CE UKCA EAC TISI
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
<b>Relative humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...3000 m
<b>Ambient air temperature for storage</b>	-15...60 °C
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage altitude</b>	0...15000 m
<b>Acoustic level</b>	58 dBA
<b>Heat dissipation</b>	2128 Btu/h
<b>IP degree of protection</b>	IP20

## Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	192 V
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	5 h
Battery life	3...5 year(s)
Battery charger power	235 W rated

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes
Free slots	1
Control panel	Multifunction LCD status and control console

## Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	48.5 cm
Package 1 Width	83.6 cm
Package 1 Length	60 cm
Package 1 Weight	79 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)