

# Product datasheet

Specifications



## APC Smart-UPS SRT 10000VA 230V

SRT10KXLI

### Overview

<b>Presentation</b>	High density, double-conversion on-line power protection with scalable runtime.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V 400 V 3 phases
<b>Other Input Voltage</b>	220 V 240 V 380 V 415 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	10000 W
<b>Rated power in VA</b>	10000 VA
<b>Output connection type</b>	6 IEC 60320 C13 3 IEC Jumpers 4 IEC 60320 C19
<b>Output connector type</b>	Hard wire 3-wire (H N + E) 1
<b>Battery type</b>	Lead-acid battery
<b>Provided equipment</b>	CD with software Documentation CD Installation guide Temperature probe USB cable Warranty card Web/SNMP management card

### General

<b>Product web sub-family</b>	High density
<b>Number of power module free slots</b>	0
<b>Number of power module filled slots</b>	0
<b>Redundant</b>	No

### Physical

<b>Colour</b>	Black
---------------	-------

Height	43.2 cm
Width	26.3 cm
Depth	71.5 cm
Net weight	111.82 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes

## Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
Input voltage limits	100...275 V adjustable (half load) 173...476 V adjustable (half load)

## Output

Maximum configurable power in W	10000 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	10000 VA

## Conformance


Product certifications	CE EAC IRAM RCM VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA

Heat dissipation	1947 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Number of battery filled slots	0
Battery recharge time	1.5 h
Number of battery replacement quantity	2
Battery voltage	+/- 192 V (split battery referenced to neutral)
Battery charger power	876 W rated
Battery power in VAh	1805 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC140</a> 
Battery option	SRT192BP2 1 3610 VAh SRT192BP2 2 5415 VAh SRT192BP2 3 7220 VAh SRT192BP2 4 9025 VAh SRT192BP2 5 10830 VAh SRT192BP2 6 12635 VAh SRT192BP2 8 16245 VAh SRT192BP2 10 19855 VAh
Extended runtime	1

## Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	480 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46.1 cm
Package 1 Width	60 cm
Package 1 Length	100 cm
Package 1 Weight	126.554 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

**Optimized Energy Efficiency**      Energy efficient product

---

**Take-back**      Take-back program available

---

## **Contractual warranty**

---

**Warranty**      3 years repair or replace (excluding battery) and 2 years for battery

**Recommended replacement(s)**