

# Product datasheet

Specifications



## APC Smart-UPS SRT 1500VA 230 V No Batteries, Used with Lithium Ion XBP, Network Card

SRT1500UXI-NCLI

### Overview

<b>Presentation</b>	High density, double-conversion on-line power protection with scalable runtime.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	1350 W
<b>Rated power in VA</b>	1500 VA
<b>Input Connection Type</b>	IEC 60320 C14
<b>Output connection type</b>	8 IEC 60320 C13
<b>Number of rack unit</b>	2U
<b>Battery type</b>	External battery system
<b>Provided equipment</b>	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card

### General

<b>Product web sub-family</b>	High density
<b>Number of power module free slots</b>	0
<b>Number of power module filled slots</b>	0
<b>Redundant</b>	No

### Physical

<b>Colour</b>	Black
<b>Height</b>	8.5 cm

<b>Width</b>	43.2 cm
<b>Depth</b>	59 cm
<b>Net weight</b>	17.51 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted with kit
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Vertical

## Input

<b>Network frequency</b>	40...70 Hz auto-sensing
<b>Input voltage limits</b>	50...150 V 40% load 80...150 V

## Output

<b>Maximum configurable power in W</b>	1350 W
<b>Harmonic distortion</b>	Less than 2 %
<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains
<b>Crest factor</b>	3 : 1
<b>UPS type</b>	Double conversion online
<b>Wave type</b>	Sine wave
<b>Bypass type</b>	Built-in bypass
<b>Maximum configurable power in VA</b>	1500 VA

## Conformance

<b>Product certifications</b>	CE EAC RCM VDE
<b>Marking</b>	CE Mark
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
<b>Relative humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage altitude</b>	0.00...15240.00 m
<b>Acoustic level</b>	50 dBA
<b>Heat dissipation</b>	450 Btu/h
<b>IP degree of protection</b>	IP20

## Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery power in VAH	0 VAh runtime
Extended runtime	1

## Communications & Management

Free slots	0
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	81 cm
Package 1 Length	60 cm
Package 1 Weight	28.21 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

## Recommended replacement(s)