

# Product datasheet

Specifications



## APC SMART-UPS SRT 2200VA 230 V NO BATTERIES, USED WITH LITHIUM ION XBP Network Card

SRT2200UXI-NCLI

### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	1980 W
Rated power in VA	2200 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Output connection type	6 IEC 60320 C13 2 IEC 60320 C19
Number of rack unit	2U
Cable length	1.83 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card

### General

Product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### Physical

Colour	Black
Height	43.2 cm

<b>Width</b>	8.5 cm
<b>Depth</b>	50.8 cm
<b>Net weight</b>	22 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted with kit
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Vertical

## Input

<b>Network frequency</b>	40...70 Hz auto-sensing
<b>Input voltage limits</b>	50...150 V 40% load 80...150 V

## Output

<b>Maximum configurable power in W</b>	1980 W
<b>Harmonic distortion</b>	Less than 2 %
<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains
<b>Crest factor</b>	3 : 1
<b>UPS type</b>	Double conversion online
<b>Wave type</b>	Sine wave
<b>Bypass type</b>	Built-in bypass
<b>Maximum configurable power in VA</b>	2200 VA

## Conformance

<b>Product certifications</b>	CE EAC
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
<b>Relative humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for storage</b>	-20...50 °C
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage altitude</b>	0.00...15240.00 m
<b>Acoustic level</b>	50 dBA
<b>Heat dissipation</b>	317 Btu/h
<b>IP degree of protection</b>	IP20

## Batteries & Runtime

<b>Number of battery filled slots</b>	0
---------------------------------------	---

Number of battery free slots	0
Battery power in VAH	0 VAh runtime
Extended runtime	1

## Communications & Management

Free slots	0
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	432 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	74.9 cm
Package 1 Length	59.4 cm
Package 1 Weight	29.6 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

## Recommended replacement(s)