

# Product data sheet

Specifications



## APC Smart-UPS, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartConnect Port +SmartSlot, AVR, LCD

SMT3000IC

### Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead time** Usually in Stock

### Main

**Main Input Voltage** 230 V

**Other Input Voltage** 220 V  
240 V

**Main Output Voltage** 230 V

**Other Output Voltage** 220 V  
240 V

**Rated power in W** 2700 W

**Rated power in VA** 3000 VA

**Input Connection Type** IEC 320 C20  
Schuko CEE 7 / EU1-16P  
BS1363A British

**Output connection type** 8 IEC 320 C13  
2 IEC Jumpers  
1 IEC 320 C19

**Number of rack unit** 0U

**Number of cables** 1

**Battery type** Lead-acid battery

**Provided equipment** USB cable

### General

**Number of power module filled slots** 0

**Number of power module free slots** 0

**Product web sub-family** Cloud-enabled monitoring

**Redundant** No

### Physical

**Colour** Black

**Height** 43.5 cm

<b>Width</b>	19.7 cm
<b>Depth</b>	54.4 cm
<b>Net weight</b>	52.5 kg
<b>Mounting location</b>	Front
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes

## Input

<b>Input voltage limits</b>	151...302 V adjustable 160...286 V
<b>Network frequency</b>	50/60 Hz +/- 3 Hz auto-sensing

## Output

<b>Harmonic distortion</b>	Less than 5 %
<b>Maximum configurable power in VA</b>	3000 VA
<b>Maximum configurable power in W</b>	2700 W
<b>Transfer time</b>	6 ms typical : 10 ms maximum
<b>UPS type</b>	Line interactive
<b>Wave type</b>	Sine wave
<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains

## Conformance


<b>Product certifications</b>	CE EAC RCM VDE
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Acoustic level</b>	53 dBA
<b>Heat dissipation</b>	375 Btu/h
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage altitude</b>	0.00...15240.00 m
<b>Relative humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %

## Batteries & Runtime

<b>Additional information</b>	Configurable for 220 : 230 or 240 nominal output voltage
<b>Extended runtime</b>	1

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	<a href="#">RBC55</a> 
Battery power in VAH	816 VAh runtime
Battery charger power	271 W rated

## Communications & Management

Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rate	365 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	69.9 cm
Package 1 Width	76.2 cm
Package 1 Length	38.1 cm
Package 1 Weight	63.7 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
----------	--

## Recommended replacement(s)