


Product datasheet

Specifications



Easy UPS 3M 80kVA 400V 3:3 UPS for internal batteries, Start-up 5x8

E3MUPS80KHBS

Overview

Presentation Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 80 kVA 3 phase UPS with advanced product features, robust electrical specifications and compact design making your business continuity easy. Ideal for small and medium data centers and other business critical applications, this UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management. This UPS is for internal batteries, but is supplied without batteries, so you can easily customize the battery runtime. For battery runtime details, see the runtime charts published under the Documents tab. Includes 5x8 start-up service.

Lead time Usually Ships within 6 Weeks

Main

Main Input Voltage 400 V 3 phases

Other Input Voltage 380 V
415 V

Main Output Voltage 400 V 3 phases

Other Output Voltage 380 V
415 V

Rated power in W 80 kW

Rated power in VA 80 kVA

Provided equipment Dust filter
Installation guide
Start-up service

Physical

Colour White (RAL 9003)

Height 197 cm

Width 60 cm

Depth 100 cm

Net weight 339 kg

USB compatible Yes

Input

Maximum input current 104 A

Max short time withstand current 10 kA

Input harmonic distortion Less than 3 % for full load

Load power factor 0.5 leading to 0.5 lagging without derating

Input Power Factor at Full Load	0.99
Input voltage limits	342...477 V
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Network frequency	40...70 Hz

Output

Maximum configurable power in VA	80 kVA
Maximum configurable power in W	80 kW
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Harmonic distortion	Less than 3 %
Output harmonic distortion	< 3% linear load and < 5% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Built-in static bypass

Conformance

Product certifications	CE EAC RCM
-------------------------------	------------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...1500 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...4572.00 m
Acoustic level	65 dBA
Heat dissipation	14850 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	VRLA
Battery voltage	240 V
Number of battery filled slots	0
Number of battery free slots	0
Max current discharge	222 A

Communications & Management

Control panel	Touch screen LCD user interface
----------------------	---------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	210.2 cm
Package 1 Width	112.5 cm
Package 1 Length	75 cm
Package 1 Weight	387 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Recommended replacement(s)