



APC Easy UPS Lithium-ion External Battery Pack for 1/2/3kVA SRVL Extended runtime model, 48V 2400Wh, 2U Rackmount

SRVL48RMBP2U

ΟV	er	VI	е	W
----	----	----	---	---

Presentation	Double-conversion On-line UPS with Lithium-lon battery to scalable runtime. Ideal UPS for essential power protection needs even in the most unstable power conditions.
I ead time	Usually in Stock

Main

Number of rack unit	2U
Battery type	Li-lon (Lithium-lon)
Provided equipment	RJ11 cable Power cable Rack mounting brackets

Safety guide

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	48 V

Physical

Colour	Black with silver front bezel
Height	8.6 cm
Width	43.8 cm
Depth	61.6 cm
Net weight	28.3 kg
Mounting mode	Rack-mounted

Conformance

Product certifications	CE	
	UKCA	
	CTP	
	UN 38.3	
	IEC 62619	

Environmental

Ambient air	temperature for
operation	

0...50 °C

Relative humidity	095 % non-condensing
Operating altitude	03000 m
Ambient air temperature for storage	-2060 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	015000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 cm
Package 1 Width	80 cm
Package 1 Length	60 cm
Package 1 Weight	33.8 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 5 years repair or replace

Recommended replacement(s)