

Product datasheet

Specifications



APC Smart-UPS Ultra, 3000VA 230V 1U, with Lithium-Ion Battery, with Network Management Card Embedded

SRTL3KRM1UINC

Overview

Presentation	Ultra high density on-line power protection with scalable runtime supported by Lithium-Ion batteries.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	230 V
Rated power in W	3000 W
Rated power in VA	3000 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Output connection type	3 IEC 320 C13 2 IEC 320 C19
Number of rack unit	1U
Cable length	2.44 m
Number of cables	1
Battery type	Li-Ion (Lithium-Ion)
Provided equipment	RJ45 cable USB cable Safety guide Rack mounting brackets Stabilization feet Screws

Batteries & Runtime

Battery recharge time	1.5 h
Number of battery replacement quantity	1
Battery voltage	50 V
Battery charger power	448 W
Battery design life	8...10 year(s)
Battery power in VAH	336 VAh runtime

Battery option	SRTL50RMBP1U-LI 1 1240 VAh SRTL50RMBP1U-LI 2 2471 VAh SRTL50RMBP1U-LI 3 3706 VAh SRTL50RMBP1U-LI 4 4944 VAh SRTL50RMBP1U-LI 5 6192 VAh
-----------------------	--

Extended runtime	1
-------------------------	---

General

Product web sub-family	High density
-------------------------------	--------------

Redundant	No
------------------	----

Physical

Colour	Silver grey
---------------	-------------

Height	43 mm
---------------	-------

Width	432 mm
--------------	--------

Depth	560 mm
--------------	--------

Net weight	15.9 kg
-------------------	---------

Mounting preference	No preference
----------------------------	---------------

Mounting mode	Rack-mounted with kit Tower-mounted with kit
----------------------	---

Two post mountable	1
---------------------------	---

USB compatible	Yes
-----------------------	-----

Mounting position	Horizontal Vertical
--------------------------	------------------------

Input

Network frequency	50/60 Hz auto-sensing
--------------------------	-----------------------

Input voltage limits	160...275 V adjustable (half load)
-----------------------------	------------------------------------

Input Power Factor at Full Load	1
--	---

Output

Maximum configurable power in W	3000 W
--	--------

Output frequency	50/60 Hz +/- 3 Hz sync to mains
-------------------------	---------------------------------

Crest factor	3 : 1
---------------------	-------

UPS type	On-Line
-----------------	---------

Wave type	Sine wave
------------------	-----------

Bypass type	Internal bypass (automatic and manual)
--------------------	--

Maximum configurable power in VA	3000 VA
---	---------

Conformance

Product certifications	CE UKCA
-------------------------------	------------

Marking	CE Mark UKCA
----------------	-----------------

Standards	EN/IEC 62040-1
------------------	----------------

Environmental

Ambient air temperature for operation	0...40 °C
--	-----------

Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dB
IP degree of protection	IP20

Communications & Management

Free slots	0
Preinstalled device	Network management card with environmental monitoring
Control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.8 cm
Package 1 Width	56.4 cm
Package 1 Length	76.4 cm
Package 1 Weight	24.2 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	5 years repair or replace
----------	---------------------------

Recommended replacement(s)