

Product data sheet

Specifications



Galaxy VS UPS 30kW 400V for External Batteries, Start-up 5x8

GVSUPS30KHS

Overview

Presentation

Highly efficient, easy-to-deploy 30kW, 400V 3-phase uninterruptible power supply (UPS) that brings best-in-class power protection to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Compact design, high-density technology and modular architecture keep total cost of ownership low and operational efficiency at the highest levels. Galaxy VS reduces your energy losses by up to 66% with the patented EConversion mode – reaching up to 99% efficiency levels and delivering more energy savings than even our industry-leading 97% efficiency in normal operating mode. The UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management via your smartphone. Includes 5x8 start-up service. For battery runtime details, see the runtime charts published under the Documents tab.

Lead time

Usually Ships within 2 Weeks

Main

Main Input Voltage	400 V 3 phase
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phase
Other Output Voltage	380 V 415 V
Rated power in W	30 kW
Rated power in VA	30 kVA
Output connector type	Hard Wire 5-wire (3PH + N + G) 1
Battery Type	External battery system Li-Ion (Lithium Ion) VRLA
Provided equipment	Dust filter Installation guide Integrated network management Power modules ship installed Start-Up Service Top and bottom cable entry

Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Battery Voltage	384-576VDC
End of Discharge Battery Voltage	307 V DC
End of Discharge Maximum Battery Current	102 A
Battery power in VAh	0 VAh runtime

Extendable Run Time	0
---------------------	---

General

Bypass Voltage Tolerance	+/- 10 %
--------------------------	----------

Max Bypass Input Current	48 A
--------------------------	------

Redundant	No
-----------	----

Physical

Color	White
-------	-------

Height	58.46 in (148.5 cm)
--------	---------------------

Width	20.51 in (52.1 cm)
-------	--------------------

Depth	33.35 in (84.7 cm)
-------	--------------------

Product Weight	454.15 lb(US) (206 kg)
----------------	------------------------

USB compatible	No
----------------	----

Input

Input Frequency	40 - 70 Hz
-----------------	------------

Number of input connectors	1 Hard Wire 4-wire (3PH + G) 1 Hard Wire 5-wire (3PH + N + G)
----------------------------	--

Efficiency at full load	340...460 V 400 V
-------------------------	-------------------

Maximum Input Current per Phase	56 A
---------------------------------	------

Maximum Short Circuit Withstand (Icw)	65 kA
---------------------------------------	-------

Input Total Harmonic Distortion	Less than 3% for full load
---------------------------------	----------------------------

Load power factor	From 0.7 leading to 0.7 lagging without any derating
-------------------	--

Input Power Factor at Full Load	0.99
---------------------------------	------

Output

Max Configurable Power (Watts)	30 kW
--------------------------------	-------

Harmonic distortion	Less than 3%
---------------------	--------------

Output Frequency (sync to mains)	50 Hz sync to mains 60 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced 50 Hz +/- 0.1 % for 50 Hz nominal not synced
----------------------------------	--

Crest factor	2.5
--------------	-----

Waveform Type	Sine wave
---------------	-----------

Output voltage tolerance	+/-1% after 50ms
--------------------------	------------------

Output Voltage THD	< 1% linear load and < 3% non-linear load
--------------------	---

Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
--------------------	---

Bypass type	Built-in Static Bypass
-------------	------------------------

Maximum configurable power in VA	30 kVA
----------------------------------	--------

Conformance

Standards	CSA C22.2 No 107.3 EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 FCC Part 15 class A IEC 60721-4-2 Level 2M2
-----------	--

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...3281 ft
Ambient Air Temperature for Storage	-13...131 °F (-25...55 °C)
Storage Relative Humidity	10...80 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	65 dBA
Online Thermal Dissipation	2922.4 Btu/h
IP degree of protection	IP21

Communications & Management

Free slots	1
Control panel	Touch Screen LCD User Interface

Ordering and shipping details

GTIN	731304342717
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	66.14 in (168 cm)
Package 1 Width	38.98 in (99 cm)
Package 1 Length	25.20 in (64 cm)
Package 1 Weight	518.09 lb(US) (235 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Under investigation
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Recommended replacement(s)