

# Product datasheet

Specifications

## Galaxy VX 1100kVA N+1 Redundant UPS, 400V, Start up 5x8



GVX1500K1100NHS

### Overview

<b>Presentation</b>	A highly efficient, modular, 1100 kVA N+1 3-phase UPS that provides the performance, flexibility, and maximized asset utilization today's large data centers and mission critical applications require. This EcoStruxure connected UPS features up to 99% efficiency in eConversion mode. Includes 5x8 start-up service.
<b>Lead time</b>	Special Order - Call for Quoted Lead Times

### Main

<b>Main Input Voltage</b>	400 V 3 phases
<b>Main Output Voltage</b>	400 V 3 phases
<b>Rated power in W</b>	1100 kW
<b>Rated power in VA</b>	1100 kVA
<b>Battery type</b>	External battery system
<b>Provided equipment</b>	Installation guide Start-up service

### Batteries & Runtime

<b>Battery voltage</b>	480 V
<b>Discharge battery voltage</b>	384 V DC
<b>Battery power in VAh</b>	0 VAh runtime
<b>Extended runtime</b>	0

### General

<b>Redundant</b>	Yes
------------------	-----

### Physical

<b>Colour</b>	White
<b>Width</b>	480 cm
<b>Product weight</b>	4190 kg
<b>USB compatible</b>	No

### Input

<b>Network frequency</b>	40...70 Hz
<b>Maximum input current</b>	1872 A

---

Load power factor	From 0.7 leading to 0.5 lagging without any derating
-------------------	--

## Output

---

Maximum configurable power in W	1100 kW
---------------------------------	---------

---

Output frequency	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
------------------	--

---

Crest factor	3 with THC <5%
--------------	----------------

---

Wave type	Sine wave
-----------	-----------

---

Output overload operation	10 minutes at 125% and 60 seconds at 150%
---------------------------	---

---

Maximum configurable power in VA	1100 kVA
----------------------------------	----------

## Conformance

---

Product certifications	C-Tick CE
------------------------	--------------

---

Standards	EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 IBC 2012 IEC 62040-4 ISTA 2B
-----------	--

## Environmental

---

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

---

Relative humidity	0...95 %
-------------------	----------

---

Operating altitude	0...3333 ft
--------------------	-------------

---

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

---

Acoustic level	69.5 dB
----------------	---------

---

Heat dissipation	185100 Btu/h
------------------	--------------

---

IP degree of protection	IP20
-------------------------	------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Weight	0.01 kg
------------------	---------

## Offer Sustainability

---

EU RoHS Directive	Under investigation
-------------------	---------------------

---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

## Contractual warranty

---

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

## Recommended replacement(s)