

# Product data sheet

Specifications



## Symmetra PX 125kW Scalable to 250kW with Right Mounted Maintenance Bypass and Distribution

SY125K250DR-PD

### Overview

**Presentation** A high-performance, 3-phase, modular, scalable, power protection solution with industry-leading efficiency, capacity, and performance for medium to large data centers and mission critical environments.

**Lead time** Usually Ships within 6 Weeks

### Main

**Main Input Voltage** 480 V 3 phases  
400 V 3 phases

**Other Input Voltage** 415 V

**Main Output Voltage** 480 V 3 phases  
400 V 3 phases

**Other Output Voltage** 415 V

**Rated power in W** 125000 W

**Rated power in VA** 125000 VA

**Output connector type** Hard wire 4-wire (3P + E) 1  
Hard wire 5-wire (3P + N + E) 1

**Battery type** VRLA

**Provided equipment** Assembly service  
Installation guide  
Network management card  
Start-up service  
User manual

### Batteries & Runtime

**Number of battery filled slots** 8

**Number of battery free slots** 0

**Battery recharge time** 3.5 h

**Number of battery replacement quantity** 6

**Battery overload operation** 10 minutes at 125% and 60 seconds at 150%

**Battery charger power** 11815 W rated

**Battery design life** 5...8 year(s)

**Battery power in VAh** 41472 VAh runtime

**Battery option** SYBFXR8-8 1 82944 VAh  
SYBFXR8-8 2 124416 VAh  
SYBFXR8-8 3 165888 VAh  
SYBFXR8-8 7 331776 VAh

SYBFXR8-8 4 207360 VAh  
SYBFXR8-8 5 248832 VAh  
SYBFXR8-8 6 290304 VAh

Extended runtime 1

## General

Bypass voltage tolerance +/- 10 % settable from +/- 4/6/8 and 10 %

Number of power module free slots 5

Number of power module filled slots 5

Redundant Yes

## Physical

Colour Black

Height 199.1 cm

Width 235 cm

Depth 107 cm

Product weight 2825 kg

USB compatible No

## Input

Network frequency 40...70 Hz auto-sensing

Number of input connectors 1 hard wire 4-wire (3P + E)  
1 hard wire 5-wire (3P + N + E)

Input voltage limits 340...460 V 400 V  
408...552 V 480 V

Max short time withstand current 50 kA

Input harmonic distortion Less than 5 % for full load

Input protection type 3-pole circuit breaker

Load power factor 0.5 leading to 0.5 lagging

Input Power Factor at Full Load 0.99

## Output

Maximum configurable power in W 250000 W

Harmonic distortion Less than 2 %

Output frequency 50 Hz sync to mains  
60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised  
50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised  
60 Hz sync to mains

UPS type Double conversion online

Wave type Sine wave

Output voltage tolerance +/- 1% static and +/- 5% at 100% load step

Output harmonic distortion < 2% linear load and < 3% non-linear load

Output overload operation 10 minutes at 125% and 60 seconds at 150%

Bypass type Built-in maintenance bypass  
Built-in static bypass

Efficiency 96 % (in battery operation)

Maximum configurable power in VA	500000 VA
----------------------------------	-----------

Transfer time	2 ms typical
---------------	--------------

## Conformance

Product certifications	cUL listed EUROBAT UL listed
------------------------	------------------------------------

Standards	CSA C22.2 No 107.3-05 EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 OSHPD UL 1778 UL 60950-1
-----------	---

## Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 %
-------------------	----------

Operating altitude	0...3333 ft
--------------------	-------------

Ambient air temperature for storage	-15...40 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0.00...15240.00 m
------------------	-------------------

Acoustic level	54 dBA
----------------	--------

Heat dissipation	15473 Btu/h
------------------	-------------

NEMA degree of protection	NEMA 1
---------------------------	--------

IP degree of protection	IP20
-------------------------	------

## Communications & Management

Free slots	1
------------	---

Preinstalled device	Network management card 2 with environmental monitoring, out of band access and Modbus
---------------------	--

Control panel	Touch screen LCD user interface
---------------	---------------------------------

Emergency power off	Optional
---------------------	----------

## Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	215 cm
------------------	--------

Package 1 Width	127 cm
-----------------	--------

Package 1 Length	299 cm
------------------	--------

Package 1 Weight	3104 kg
------------------	---------

## Offer Sustainability

EU RoHS Directive	Not compliant
-------------------	---------------

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
---------------------------	---

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

# Contractual warranty

---

Warranty 1 year on-site repair or replace with factory authorized Start-Up

Recommended replacement(s)