

Product datasheet

Specifications



Symmetra PX 160kW 400V w/ Integrated Modular Distribution

SY160K160H-PD

Overview

Presentation	A high-efficiency 3-phase UPS with integrated modular distribution that can be right-sized to your data center power requirements. With scalable power, distribution and run-time, this UPS grows with your data center up to 160kW/160kVA. Suitable for small to medium data centers or individual zones of large data centers.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	230 V 400 V 3 phases
Rated power in W	160000 W
Rated power in VA	160000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Battery type	VRLA
Provided equipment	Network management card Start-up service User manual

Batteries & Runtime

Number of battery filled slots	15
Number of battery free slots	3
Battery recharge time	3.5 h
Number of battery replacement quantity	4
Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery voltage	+/- 192 V (split battery referenced to neutral)
Discharge battery voltage	+/- 154 V
Overcurrent protection	945 A
Maximum short-circuit current	10 kA
Max current discharge	550 A
Battery overload operation	10 minutes at 125% and 60 seconds at 150%
Battery charger power	14769 W rated
Battery design life	5...8 year(s)

Battery power in VAH	51840 VAh runtime
Battery option	SYBT9-B4 3 62208 VAh SYCFXR9-9 1 93312 VAh SYCFXR9-9 2 124416 VAh

Extended runtime	1
-------------------------	---

General

Bypass wiring configuration	5 wire (3P + N + E)
------------------------------------	---------------------

Max bypass input current	250 A
---------------------------------	-------

Bypass current protection	250 A
----------------------------------	-------

Number of power module free slots	0
--	---

Number of power module filled slots	10
--	----

Redundant	Yes
------------------	-----

Physical

Colour	Black
---------------	-------

Height	199.1 cm
---------------	----------

Width	180 cm
--------------	--------

Depth	107 cm
--------------	--------

Product weight	2878 kg
-----------------------	---------

USB compatible	No
-----------------------	----

Input

Network frequency	40...70 Hz
--------------------------	------------

Number of input connectors	1 hard wire 5-wire (3P + N + E)
-----------------------------------	---------------------------------

Input voltage limits	340...477 V
-----------------------------	-------------

Maximum input current	295 A
------------------------------	-------

Switching current capacity	315 A
-----------------------------------	-------

Max short time withstand current	30 kA
---	-------

Input harmonic distortion	Less than 5 % for full load
----------------------------------	-----------------------------

Load power factor	0.5 leading to 0.5 lagging
--------------------------	----------------------------

Input Power Factor at Full Load	0.99
--	------

Output

Maximum configurable power in W	160000 W
--	----------

Harmonic distortion	Less than 2 %
----------------------------	---------------

Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
-------------------------	--

UPS type	Double conversion online
-----------------	--------------------------

Wave type	Sine wave
------------------	-----------

Output voltage tolerance	+/- 1% static and +/- 5% at 100% load step
---------------------------------	--

Output harmonic distortion	< 2% for 0 to 100% linear load and < 6% for full non-linear load
-----------------------------------	--

Output overload operation	10 minutes at 125% and 60 seconds at 150%
----------------------------------	---

Required output current protection	250 A
Neutral output current	400 A
Bypass type	Built-in static bypass
Efficiency	94 % (in battery operation)
Maximum configurable power in VA	160000 VA

Conformance

Product certifications	EUROBAT
Standards	EN 50091-1 EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 ISO 14001 ISO 9001 VFI-SS-111

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	63 dBA
Heat dissipation	28741 Btu/h
NEMA degree of protection	NEMA 1
IP degree of protection	IP20

Communications & Management

Free slots	2
Preinstalled device	Network management card with CAN
Control panel	Multifunction LCD status and control console
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	214 cm
Package 1 Width	121 cm
Package 1 Length	223.5 cm
Package 1 Weight	3116 kg

Offer Sustainability

EU RoHS Directive	Under investigation
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty 1 year on-site repair or replace with factory authorized Start-Up

Recommended replacement(s)