

Product data sheet

Specifications



Symmetra PX 96kW, without Bypass, Distribution, or Batteries, 400V

SY96K96H-NB

Overview



Presentation	A high-efficiency, modular 3-phase UPS that offers internal redundancy for your data center requirements. With scalable power, this UPS grows with your data center up to 160kW/kVA. Pair with the Classic Battery Cabinet and the Wall-Mount or 300mm Maintenance Bypass Panel to complete your power protection solution. Please click here for Classic Battery Cabinet runtime information. Suitable for small to medium data centers or individual zones of large data centers.
---------------------	--

Lead time	Usually Ships within 3 Weeks
------------------	------------------------------

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	230 V 400 V 3 phases
Rated power in W	96000 W
Rated power in VA	96000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Battery type	External battery system
Provided equipment	Network management card Start-up service User manual

Batteries & Runtime

Number of battery free slots	0
Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery power in VAh	0 VAh runtime
Extended runtime	0
Replacement battery	SYPBV96K160HA  SYPBV96K160HB 

General

Bypass wiring configuration	5 wire (3P + N + E)
Max bypass input current	250 A
Bypass current protection	250 A
Number of power module free slots	4

Number of power module filled slots	6
-------------------------------------	---

Redundant	Yes
-----------	-----

Physical

Colour	Black
--------	-------

Height	199.1 cm
--------	----------

Width	60 cm
-------	-------

Depth	107 cm
-------	--------

Product weight	496 kg
----------------	--------

USB compatible	No
----------------	----

Input

Network frequency	40...70 Hz
-------------------	------------

Number of input connectors	1 hard wire 5-wire (3P + N + E)
----------------------------	---------------------------------

Input voltage limits	340...477 V
----------------------	-------------

Maximum input current	197 A
-----------------------	-------

Switching current capacity	315 A
----------------------------	-------

Max short time withstand current	30 kA
----------------------------------	-------

Input harmonic distortion	Less than 5 % for full load
---------------------------	-----------------------------

Load power factor	0.5 leading to 0.5 lagging
-------------------	----------------------------

Input Power Factor at Full Load	0.99
---------------------------------	------

Output

Maximum configurable power in W	96000 W
---------------------------------	---------

Harmonic distortion	Less than 2 %
---------------------	---------------

Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
------------------	--

UPS type	Double conversion online
----------	--------------------------

Wave type	Sine wave
-----------	-----------

Output voltage tolerance	+/- 1% static and +/- 5% at 100% load step
--------------------------	--

Output harmonic distortion	< 2% for 0 to 100% linear load and < 5% for full non-linear load
----------------------------	--

Output overload operation	10 minutes at 125% and 60 seconds at 150%
---------------------------	---

Required output current protection	250 A
------------------------------------	-------

Neutral output current	240 A
------------------------	-------

Bypass type	Built-in static bypass
-------------	------------------------

Efficiency	95 % (full load) 95 % (half load) 94 % (in battery operation)
------------	---

Maximum configurable power in VA	160000 VA
----------------------------------	-----------

Conformance

Standards	EN 50091-1 EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3
-----------	--

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 %
-------------------	----------

Operating altitude	0...3333 ft
--------------------	-------------

Ambient air temperature for storage	-15...40 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0.00...15240.00 m
------------------	-------------------

Acoustic level	63 dBA
----------------	--------

Heat dissipation	17244 Btu/h
------------------	-------------

NEMA degree of protection	NEMA 1
---------------------------	--------

IP degree of protection	IP20
-------------------------	------

Communications & Management

Free slots	2
------------	---

Preinstalled device	Network management card with CAN
---------------------	----------------------------------

Control panel	Multifunction LCD status and control console
---------------	--

Emergency power off	Yes
---------------------	-----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	214 cm
------------------	--------

Package 1 Width	121 cm
-----------------	--------

Package 1 Length	84.8 cm
------------------	---------

Package 1 Weight	547 kg
------------------	--------

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Recommended replacement(s)