

APC NetShelter Rack PDU Advanced, Switched, 7.4kW, 1PH, 230V, 32A, 332P6, 40 Outlet

APDU10150SW

Overvie	2171

**Lead time** Usually in Stock

#### Main

iviaiii	
Main Input Voltage	230 V 3 phases
Product or component type	PDU
PDU type	Switched
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 2P + PE
Number of rack unit	0U
Cable length	3.0 m
Communication port protocol	1000BASE-T 10/100BASE-T

## **Physical**

Colour	Black
Height	149.0 cm
Width	5.6 cm
Depth	7.5 cm
Net weight	7.4 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Vertical

## Input

[In] rated current	32 A
Permissible voltage	200240 V
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz

# Output

Number of power socket outlets	20 C13/C15/C19/C21
•	20012/015

## Conformance

Product certifications	UKCA TAA compliance
Standards	CE EN 62368-1

## **Environmental**

Ambient air temperature for operation	-560 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.0015240.00 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	172 cm
Package 1 Width	11.6 cm
Package 1 Length	20.8 cm
Package 1 Weight	9.4 kg

# Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

# **Contractual warranty**

Warranty	3 years repair or replace	
* * arranty	o yours repair or replace	

#### Recommended replacement(s)