

Product datasheet

Specifications



APC NetShelter Rack PDU Advanced, Switched Metered Outlet, 3PH, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

APDU10350SM

Overview

Lead time Usually in Stock

Main

Main Input Voltage	415 V 3 phases 400 V 3 phases
Product or component type	PDU
PDU type	Switched metered outlet
Main Output Voltage	240 V
Input Connection Type	IEC 60309 30 A 3P + N + PE
Number of rack unit	0U
Cable length	1.8 m
Communication port protocol	1000BASE-T 10/100BASE-T

Physical

Colour	Black
Height	178.0 cm
Width	5.6 cm
Depth	7.5 cm
Net weight	9.6 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Vertical

Input

[In] rated current	24 A
Permissible voltage	200...240 V 346...415 V
Input current limits	30 A
Load capacity	17300 VA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Network frequency	50/60 Hz
-------------------	----------

Output

Number of power socket outlets	24 C13/C15/C19/C21 24C13/C15
--------------------------------	---------------------------------

Conformance

Product certifications	UKCA TAA compliance
------------------------	------------------------

Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1
-----------	---

IP degree of protection	IP44
-------------------------	------

Environmental

Ambient air temperature for operation	-5...60 °C
---------------------------------------	------------

Relative humidity	5...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage altitude	0.00...15240.00 m
------------------	-------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	198 cm
------------------	--------

Package 1 Width	13.2 cm
-----------------	---------

Package 1 Length	26.2 cm
------------------	---------

Package 1 Weight	12.6 kg
------------------	---------

Offer Sustainability

REACH Regulation	REACH Declaration
------------------	-----------------------------------

REACH free of SVHC	Yes
--------------------	-----

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
-----------------------	---

RoHS exemption information	Yes
----------------------------	---------------------

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Recommended replacement(s)