
# Product datasheet

Specifications



## Easy UPS Dry Contact Card/Relay I/O card

VGL9901I

## Overview

| | |
|---|---|
| **Presentation** | High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions. |

## Main

| | |
|---|---|
| **Product or component type** | Communication module |
| **Provided equipment** | User manual |
| **Range of product** | Easy UPS On-Line |

## Physical

| | |
|---|---|
| **Height** | 26 mm |
| **Width** | 52 mm |
| **Depth** | 84 mm |
| **Net weight** | 0.05 kg |
| **Mounting mode** | Not rack-mountable |

## Environmental

| | |
|---|---|
| **Ambient air temperature for operation** | 0…40 °C |
| **Relative humidity** | 0…95 % |
| **Ambient air temperature for storage** | -15…45 °C |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 5.000 cm |
| **Package 1 Width** | 12.500 cm |
| **Package 1 Length** | 17.000 cm |
| **Package 1 Weight** | 141.300 g |
| **Unit Type of Package 2** | S01 |
| **Number of Units in Package 2** | 4 |
| **Package 2 Height** | 15.000 cm |
| **Package 2 Width** | 15.000 cm |
| **Package 2 Length** | 40.000 cm |
| **Package 2 Weight** | 706.000 g |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Unit Type of Package 3** | P06 |
| **Number of Units in Package 3** | 128 |
| **Package 3 Height** | 75.000 cm |
| **Package 3 Width** | 80.000 cm |
| **Package 3 Length** | 60.000 cm |
| **Package 3 Weight** | 30.602 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 12 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **35 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **2 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **0 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **9 540 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **0 kg CO2 eq.** |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | Compliant |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **95** |
| End of life manual availability | End of Life Information |
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins** |

Image of product / Alternate images

**Alternative**

